

Transition from flat to curved HMI designs



Next-Generation IMD/FIM Hard Coated Film

LevSurf_™ is a hard-coated substrate for film insert molding (IMD/FIM) that enables 3D forming. While conventional hard coated materials can only be used for flat designs, the new LevSurf_™ series enables seamless three dimensional designs in addition to the durability of hard coated films.

F04 / F18 / F13

LevSurf[™] is a pre-UV cured hard coating, which offers advan-

Forming

Semi cured surface is sensitive to denting, scratching and adhesion of foreign materials. This decreases yield and quality.

Forming

Short lead times, higher yield and productivity, stable quality.

(3) Curing

niection

Process

reduction

LevSurf TM Process Advantage

tages during the manufacturing process.

Printing 2

6

Printing

 \bigcirc

 \odot

LevSurf[™] is a UV cured film for film insert molding (IMD/FIM) with excellent hardness and formability. Due to the high optical quality it can substitute display glass, lowering the vehicle weight and therefore contributing to the reduction of cost and CO2 emissions.

> Conventional Post-UV curing

LevSurf

molding proces

printing and

process

Excellent form- and stretching properties

This product is processed at temperatrues between 160-170°C with great formability in high pressure and vacuum forming.

LevSurf...

Tight edges and curves are possible without degrada-Standard hard coatings will tion of the optical quality. display an increase in haze

Conventional products

or even create cracks







*Square size 5mm, 160°C-170°C vacuum and pressure molded

Product Line-up

We offer three standard products to match your project requirements.



Sun screen, hand cream, acetone, methyl ethyl ketone, alcohol, hydrochloric acid, sodium hydroxide solution, cleaning solution, artificial sweat solution, beverages



KIMOTO Co., Ltd. office030@kimoto.co.jp

INQUIRIES